

20CFO-SWDS-HV

20" High Velocity Washdown Duty Fan



Air Velocity (@ 5 times diameter) :	1280	Frame Size :	56C
Blade Color :	Metallic	Frequency (Hz) :	60
Blade Material :	Stainless Steel	Guard Color :	Metallic
Blade Pitch (degrees) :	26	Guard Material & Coating :	Stainless Steel
Bore Size (inches) :	5/8	Guard Spacing (inches) :	1/2 OSHA
CFM (free air) :	5200	Max RPM :	1725
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Mount Type Recommended :	SS Wall Mounts
CFM Range (Free Air) :	5001 - 10000	Nameplate Amps :	8.2/4.1
CFM/Watt (free Air) :	13.6	Number of Wings :	3
CFM/Watt Range (free air) :	2/3	Oscillating :	No
Component Certifications :	Motor - UL/CSA/CE	Phase :	1
Cord :	Not included	Power (hp) :	1/2
Country of Origin :	US	Product Color :	Metallic
Description :	[TBO] Fan Circulation 20" OSHA Stainless Steel Guard w/ 1/2 HP Stainless Steel Motor & Stainless Steel Blade	Product Weight (pounds) :	41
Diameter (inches) :	20	Speed Control Compatible :	No
Distinguishing Feature - Fan :	Washdown Duty	Speeds :	1
Drive Type :	Direct	Thermal Protection :	No
Enclosure :	TEFC	VFD Compatible :	No
Fixed or Portable :	Fixed	Voltage :	115/230