

TW24W-PRB

24" Oscillating OSHA Pedestal Fan



Air Velocity (@ 10') :	900	Guard Material & Coating :	Powder Coated Steel
Blade Color :	Metallic	Guard Spacing (inches) :	1/2 OSHA
Blade Material :	Aluminum	Max RPM :	1075
Brand :	Schaefer	Mount Type Included :	Pedestal
CFM (free air) :	5400	Mount Type Recommended :	NA
CFM (high) :	5400	Nameplate Amps :	3
CFM (low) :	4900	Number of Wings :	3
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Opening Area (sq. ft.) :	NA
CFM Range (Free Air) :	5001 - 10000	Oscillating :	Yes
CFM/Watt (free Air) :	20.8	Phase :	1
CFM/Watt Range (free air) :	20.1 - 25	Power (hp) :	1/2
Cord :	Included - Wired	Rough-in Dimensions :	NA
Cord Length (feet) :	10	Schaefer Performance Test No. :	694
Country of Origin :	US	Sound Level (dBA @ 10') :	64
Description :	24" Oscillating Circulation Fan, White OSHA Guards, Black Round Pedestal	Speed Control Compatible :	No
Diameter (inches) :	24	Speeds :	2
Drive Type :	Direct	Switch :	On product
Fixed or Portable :	Portable	VFD Compatible :	No
Frequency (Hz) :	60	Voltage :	115
Guard Color :	White		