

## 20CFO 20" Circulation Fan



Able to Ship Small Parcel :	Yes	Guard Spacing (inches) :	1/2 OSHA
Blade Color :	Metallic	Max RPM :	1100
Blade Material :	Aluminum	Mount Type Recommended :	WMTA24-B, VS24FMT
CFM (high) :	4050	Nameplate Amps :	2.9/1.6
CFM (low) :	3000	Number of Wings :	3
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Oscillating :	No
CFM Range (Free Air) :	2501 - 5000	Phase :	1
CFM/Watt (free Air) :	17.7	Power (hp) :	1/4
Component Certifications :	Motor - CSA	Product Color :	White
Cord :	Included - Wired	Product Dimensions (L x W x H inches) :	22.5 x 6.25 x 12 in.
Cord Length (feet) :	10	Product Shipping Dimensions :	24 X 24 X 13
Country of Origin :	US	Product Weight (pounds) :	30
Diameter (inches) :	20	Schaefer Performance Test No. :	101
Display Name :	20CFO	Speed Control Compatible :	No
Drive Type :	Direct	Speeds :	2
Fixed or Portable :	Fixed	Switch :	On product
Frequency (Hz) :	60	VFD Compatible :	No
Guard Color :	White	Voltage :	115
Guard Material & Coating :	Powder Coated Steel		