

FFM365A34-3-HL

36" Fiberglass Belt Drive Hazardous Location Exhaust Fan



Blade Color :	Metallic	Guard Material & Coating :	Powder Coated Steel
Blade Material :	Aluminum	Guard Spacing (inches) :	1 - 2
Blade Pitch (degrees) :	37	Housing Color :	White
CFM (free air) :	9500	Housing Material :	Fiberglass
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Max RPM :	1725
CFM Range (Free Air) :	5001 - 10000	Nameplate Amps :	2.8-2.9/1.4
Component Certifications :	Motor - UL/CSA	Number of Wings :	5
Cord :	Not included	Oscillating :	No
Country of Origin :	US	Phase :	3
Diameter (inches) :	36	Power (hp) :	1/2
Display Name :	FFM365A34-3-HL	Product Color :	White
Distinguishing Feature - Fan :	Hazardous Location Rated	Rough-in Dimensions :	43 1/2" x 43 3/4"
Drive Type :	Belt	Speed Control Compatible :	No
Enclosure :	TEFC	Speeds :	1
Fixed or Portable :	Fixed	Thermal Protection :	Yes
Frequency (Hz) :	60	VFD Compatible :	No
Guard Color :	Black	Voltage :	208-230/460