

TW20B-TPQR

20" Oscillating OSHA Pedestal Fan



Air Velocity (@ 10') :	650	Guard Material & Coating :	Powder Coated Steel
Blade Color :	Metallic	Guard Spacing (inches) :	1/2 OSHA
Blade Material :	Aluminum	Mount Type Recommended :	NA
CFM (free air) :	4100	Nameplate Amps :	3.0/3.7
CFM (high) :	4100	Number of Wings :	3
CFM (low) :	3400	Opening Area (sq. ft.) :	NA
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Oscillating :	No
CFM Range (Free Air) :	2501 - 5000	Phase :	1
CFM/Watt (free Air) :	22.8	Power (hp) :	1/4
Component Certifications :	Motor - CSA	Product Color :	Black
Cord :	Included - Wired	Rough-in Dimensions :	NA
Cord Length (feet) :	10	Schaefer Performance Test No. :	698
Country of Origin :	US	Sound Level (dBA @ 10') :	63.5
Diameter (inches) :	20	Speed Control Compatible :	No
Display Name :	TW20B-TPQR	Speeds :	2
Drive Type :	Direct	Switch :	On product
Fixed or Portable :	Portable	VFD Compatible :	No
Frequency (Hz) :	60	Voltage :	115
Guard Color :	Black		