

## TW20W

### 20" Oscillating Circulation Fan



Able to Ship Small Parcel :	Yes	Guard Color :	White
Air Velocity (@ 10') :	650	Guard Material & Coating :	Powder Coated Steel
Blade Color :	Metallic	Guard Spacing (inches) :	1/2 OSHA
Blade Material :	Aluminum	Mount Type Recommended :	WMTA24-B, VS24FMT
CFM (high) :	4100	Nameplate Amps :	3
CFM (low) :	3400	Number of Wings :	3
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Oscillating :	Yes
CFM Range (Free Air) :	2501 - 5000	Phase :	1
CFM/Watt (free Air) :	14	Power (hp) :	1/4
Component Certifications :	Motor - UL/CSA/CE	Product Color :	White
Cord :	Included - Wired	Product Weight (pounds) :	33
Cord Length (feet) :	10	Schaefer Performance Test No. :	101
Country of Origin :	US	Sound Level (dBA @ 10') :	63.5
Diameter (inches) :	20	Speed Control Compatible :	No
Display Name :	TW20W	Speeds :	2
Drive Type :	Direct	Switch :	On product
Fixed or Portable :	Fixed	VFD Compatible :	No
Frequency (Hz) :	60	Voltage :	115