

## TW24HVB-TPQR

24" High Velocity Oscillating OSHA Pedestal Fan



Air Velocity (@ 10') :	950	Guard Material & Coating :	Powder Coated Steel
Blade Color :	Metallic	Guard Spacing (inches) :	1/2 OSHA
Blade Material :	Aluminum	Mount Type Recommended :	NA
CFM (free air) :	6700	Nameplate Amps :	5.9
CFM (high) :	6700	Number of Wings :	3
CFM (low) :	6200	Opening Area (sq. ft.) :	NA
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Oscillating :	No
CFM Range (Free Air) :	5001 - 10000	Phase :	1
CFM/Watt (free Air) :	15.8	Power (hp) :	1/2
Component Certifications :	Motor - UL/CSA/CE	Product Color :	Black
Cord :	Included - Wired	Rough-in Dimensions :	NA
Cord Length (feet) :	10	Schaefer Performance Test No. :	721
Country of Origin :	US	Sound Level (dBA @ 10') :	68
Diameter (inches) :	24	Speed Control Compatible :	No
Display Name :	TW24HVB-TPQR	Speeds :	2
Drive Type :	Direct	Switch :	On product
Fixed or Portable :	Portable	VFD Compatible :	No
Frequency (Hz) :	60	Voltage :	115
Guard Color :	Black		