

TW24W-PRB

24" Oscillating OSHA Pedestal Fan



Air Velocity (@ 10') :	900	Guard Spacing (inches) :	1/2 OSHA
Blade Color :	Metallic	Max RPM :	1075
Blade Material :	Aluminum	Mount Type Included :	Pedestal
CFM (free air) :	5400	Mount Type Recommended :	NA
CFM (high) :	5400	Nameplate Amps :	3.0
CFM (low) :	4900	Number of Wings :	3
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Opening Area (sq. ft.) :	NA
CFM Range (Free Air) :	5001 - 10000	Oscillating :	Yes
CFM/Watt (free Air) :	20.8	Phase :	1
Cord :	Included - Wired	Power (hp) :	1/2
Cord Length (feet) :	10	Rough-in Dimensions :	NA
Country of Origin :	US	Schaefer Performance Test No. :	694
Diameter (inches) :	24	Sound Level (dBA @ 10') :	64
Display Name :	TW24W-PRB	Speed Control Compatible :	No
Drive Type :	Direct	Speeds :	2
Fixed or Portable :	Portable	Switch :	On product
Frequency (Hz) :	60	VFD Compatible :	No
Guard Color :	White	Voltage :	115
Guard Material & Coating :	Powder Coated Steel		