

VAF3000A-2

Americ Confined Space Ventilator 2 Speed



Able to Ship Small Parcel :	Yes	Guard Spacing (inches) :	1/2 OSHA
Blade Color :	Black	Housing Color :	Blue
Blade Material :	Polypropylene	Housing Material :	Polyethylene
CFM (free air) :	2780	Maximum Duct Length (feet) :	125
CFM (high) :	2780	Maximum Static Pressure (in. H2O) :	3
CFM (low) :	1875	Nameplate Amps :	10/6.7
CFM Calculation Standard :	ANSI/AMCA Standard 230-99	Number of Wings :	7
CFM Range (Free Air) :	2501 - 5000	Oscillating :	No
CFM/Watt (free Air) :	3.6	Phase :	1
Component Certifications :	Motor - UL/CSA	Power (hp) :	1
Cord :	Included - Wired	Product Certifications :	cULus
Cord Length (feet) :	20	Product Color :	Blue
Country of Origin :	US	Product Dimensions (L x W x H inches) :	21" x 17" x 14"
Diameter (inches) :	12	Product Weight (pounds) :	33
Display Name :	VAF3000A-2	RPM 50 Hz Motor :	2000-2600
Distinguishing Feature - Fan :	Suitable with Ducting	RPM 60 Hz Motor :	3000-3600
Drive Type :	Direct	Schaefer Performance Test No. :	0789 / 0790
Fixed or Portable :	Portable	Sound Level (dBA @ 10') :	82
Frequency (Hz) :	60	Speeds :	2
Guard Color :	Black	Switch :	On product
Guard Material & Coating :	Powder Coated Steel	Voltage :	115