

VAF8000B-3

Americ Confined Space Ventilator



| | | | |
|--------------------------------|---------------------------|---|-----------------------|
| Able to Ship Small Parcel : | No | Guard Material & Coating : | Powder Coated Steel |
| Blade Color : | Black | Guard Spacing (inches) : | 1/2 OSHA |
| Blade Material : | Polypropylene | Housing Color : | Blue |
| CFM (free air) : | 9968 | Housing Material : | Polyethylene |
| CFM (with 25' of duct) : | 9380 | Maximum Duct Length (feet) : | >125 |
| CFM Calculation Standard : | ANSI/AMCA Standard 230-99 | Maximum Static Pressure (in. H2O) : | 6 |
| CFM Range (Free Air) : | 5001 - 10000 | Nameplate Amps : | 6.5 |
| Component Certifications : | Motor - UL/CSA | Number of Wings : | 5 |
| Cord : | Included - Wired | Oscillating : | No |
| Cord Length (feet) : | 20 | Phase : | 3 |
| Country of Origin : | US | Power (hp) : | 5 |
| Diameter (inches) : | 20 | Product Color : | Blue |
| Display Name : | VAF8000B-3 | Product Dimensions (L x W x H inches) : | 27.5" x 27.5" x 25.5" |
| Distinguishing Feature - Fan : | Suitable with Ducting | Product Weight (pounds) : | 119 |
| Drive Type : | Direct | Schaefer Performance Test No. : | Schaefer |
| Fixed or Portable : | Portable | Speeds : | 1 |
| Frequency (Hz) : | 60/50 | Switch : | On product |
| Guard Color : | Black | Voltage : | 440 |