

Sensorex TX10 AND TX20 TRANSMITTERS

PRODUCT SPECIFICATION SHEET

pH AND ORP TRANSMITTERS/CONTROLLERS IN 1/8 DIN ENCLOSURES



SPECIFICATIONS

pH Buffer Recognition	US (4.01, 7.00, 10.01) or NIST (4.00, 6.86, 9.18), user selectable
pH Electrode Offset Recognition	\pm 100mV at pH 7.00 / -91.7mV to 108.3mV at pH 6.86
pH Electrode Slope Recognition	± 30% at pH 4.00, 4.01, 9.18 or 10.01
Temperature Compensation	Auto/Manual -10.0-120°C
Input Impedance	>10 ¹³ ohms
Input Select	User selectable pH or ORP
Control Type / Relay Output (TX20)	2 ON/OFF controls / 5A at 115VC AC or 2.5A at 220V AC, resistive load only
Current Output Range/ Scale (TX10)	4-20mA (isolated) / Linear
Maximum Load	500 ohm
Isolation Voltage	500 VDC
Display	LCD with back-lighting
Power	100-240 VAC at 50/60 Hz
Ambient Temperature Range	0-50°C
Case	1/8 DIN, 90mm depth

Clear LCD displays pH or ORP and temperature

Easy to install 1/8 DIN plastic enclosure

Universal power supply input from 100-240VAC

Automatic US and NIST buffer recognition

Two sets of programmable on/off relays (TX20)

Or isolated, reversible 4-20mA current output (TX10)

The TX10 and TX20 transmitter series offers a costeffective, small footprint solution for pH and ORP process control. Save space in your panel with either of these 1/8 DIN size models. The simple and easy to understand user interface features a four button membrane keypad for quick set up and programming. The TX10 has an isolated, reversible 4-20mA current output, providing versatility for a wide range of process control applications. The TX20 features two sets of programmable on/off relays, allowing the device to control warning lights, alarms or other process control systems. Both models feature a large, clear LCD panel display for quick and easy reference to pH, or ORP, or temperature.

RESOLUTION AND ACCURACY

	Range	Resolution	Accuracy
рН	-2.00 to 16.00 pH	0.01 pH	± 0.1% ± 1 digit
ORP	-1999 to 1999 mV	1 mV	± 0.1% ± 1 digit
Temperature	-10.0 to 120.0°C	0.1°C	± 0.3°C

ORDERING INFORMATION

Part Number	Description
TX10	4-20mA pH and ORP transmitter in 1/8 DIN case or enclosure
TX20	pH and ORP Transmitter/controller with two sets of programmable on/off relays in 1/8 DIN enclosure