

**TECHNICAL DATA SPECIFICATIONS
TM INDUCTION HEATING**



EASYTHERM 15 HQ* or Standard Models

Benchtop Induction Heater with Swingarm


***HQ Models are UL approved by TUV**



TECHNICAL DATA SPECIFICATIONS TM INDUCTION HEATING



TECHNICAL SPECIFICATIONS: EASYTHERM 15

 <p>US HQ MODELS</p> <p>The Easytherm 15 is a powerful 480Volt microprocessor controlled induction heater with an ergonomic pivoting yoke used to professionally mount a range of parts including bearings. Typically used in maintenance shops and production environments.</p> <p>Warranty: 36 months</p> <p>Delivery: Normal Stock Net 30 FOB Denver</p> <p>Rick Trichka TM Induction Heating US Sales 720-266-4403 Office • 720-838-5980 Mobile • 303-646-4880 Fax</p>	Description	Metric	US/UK	
	Power Rating	15.3kVA		
	Voltage / Current	480/32		
	Optional Voltage	240/575		
	Frequency	50-60Hz		
	Swing Arm	Yes		
	Plug	No		
	Max Weight			
	Bearing	150kg	330 lbs.	
	Other	150kg	330 lbs	
	Min. Bore	30mm	1.18"	
	Max. Outside	515mm	19.29"	
	Max. Part Width	210mm	8.26"	
	Vertical Post Section			
	Width	210mm	8.26"	
	Height	215mm	8.46"	
	Power Regulation	Yes 0-100% Automatic		
	Temperature Control	Yes (0-240°C)	(0-464°F)	
	Time Control	Yes (0-99 min.)		
	De Magnetize	Yes <2 A/cm		
	Alarm	Yes		
	Temperature Hold	Yes		
	Thermal Safety Switch	Yes		
	Temp Probe	Yes – Mag. Probe		
	IR Remote Control	Available HQ Only		
	Digital Display – Time	Yes		
	Digital Display – Temp	Yes (C/F)		
	Digital Display – Error	Yes		
Communications	N/A			
Aux Input/Output	Available			
Yokes Included			20/40/70	
Available Yokes	20x350mm (min bore 30mm) 30x350mm (min bore 45mm) 40x350mm (min bore 55mm) 50x350mm (min bore 70mm) 60x350mm (min bore 85mm) 70x350mm (min bore 100mm)			