LINKALIGHT

by Western Technology


LED Wide Area
"Stringer Light"
* THEY CONNECT *



Designed + Manufactured in the USA

Model 4400 - LED Wide Area Stringer Light System

July 2020






Quantity of Lightheads vs. Total Cable Length

14AWG Cable (20A plug @16A current rating)				
Total Cable Length (ft):	50'	100'	150'	200'
# of Lightheads:	32	26	20	13

	*Product Features		
Light Output:	Variable Intensity Control (Dimmer): with a continuous range in Luminous Flux: 600 to +6,000 lumens		
Brightness:	High: ~4,000 Lux Low: ~400 Lux @ 1ft		
Reflective Optic Angle:	~75° (Floodlight projection)		
Observed Beam Angle:	~100° (Floodlight projection)		
Light Source:	COB LED		
Color Temperature:	~5700K, 70CRI		
Power Input:	120-277 VAC, 50/60 Hz		
Material/ Construction:	Light Body: machined from solid blocks of 6061-T6 Aluminum		
	Bumpers: Polyurethane		
Dimensions:	8.0" Length x 4.25" Width x 4.25" Depth		
Weight:	Lighthead: ~5.3 lbs		
Special Features:	Blast Shields, Diffusers, Dome Diffusers		
	Variety of mounting options available		
	Thermally regulated for safe handling		









*Equipment specifications, options & availability subject to change





Western Technology, Inc. 3517 Arsenal Way Bremerton, WA 98312 Toll Free: (800) 654-5483 Local: (360) 917-0080 Fax: (360) 917-0083

www.WesternTechnologyLights.com