THE STRINGER

Optional Configuration of The BRICKette™



Designed + Manufactured in America

The BRICKette™: 2106 LED- Explosion Proof Work Light





Multiple Mounting **Options**

Magnetic, Solid, or Slotted Handles-(See The BRICKette™ Datasheet for more info)



Product Features

▶ Approved for: Class I, Div 1 & 2, Group C & D

▶ Approved for: Class II, Div 1 & 2, Group E, F, & G

▶ **Approved for:** CSA Zones 1 & 2; Zones 20, 21, & 22

Conforms to: UL Stds 153, 8750, 844:

▶ Certified to: CSA Stds C22.2#s 12, 25, 30, 137, 250.13

► Suitable for Wet Location Use: Type 6P

► Certified: Portable Luminary

► Temperature Rating: T-code: T5 (-25° to +40°C)

▶ **LED Color:** ~6000K, CRI >70

Rated with optics: 26,000 lux at 1'

Rated with optics: >2,500 lumens

► Reflective Optic Beam Angle: 60°

▶ Light Head Power: 21VDC, 800mA, LVLE

▶ Weight: 3.5 lbs (light head only) | 4.2-5.3 lbs (light head with handle)

▶ **Dimensions:** 6"L x 2.9"W x 2.3"H

▶ Protection: Polyurethane Bumper

Accessories: Blast Shields, Dome Diffuser, Overspray Protection Bags

Variable Mounting Options: Magnetic, Solid and Slotted Handles (High & Low Profiles, Short and Long Handles)









Western Technology, Inc. Bremerton, WA 98312 Fax: (360) 917-0083

Toll Free: (800) 654-5483 3517 Arsenal Way Local: (360) 917-0080

www.WesternTechnologyLights.com