

OI-7543K Gen II WireFree Monitor/Sensor Assembly Kit

The The GenII OI-7543 is a WireFree 4-channel receiver specifically designed for use in conjunction with Otis Instruments, Inc. GenII WireFree Sensor Assemblies.

The OI-7543K is a customizable kit with up to two pre-mounted alarms (light/horn), and up to two Gen II WireFree sensor assemblies (OI-6900).



OI-7543K Features & Benefits

- Pre-mounted alarms (light and horn shown here) for quicker, easier installation
- Customizable kit with either one or two CSA and ATEX Certified OI-6900 Sensor Assemblies, featuring:
 - Non-intrusive calibration
 - Glass lid for viewing amplifier display
 - Rapid response and clearing time
- Compatible with pre-existing Gen II WireFree sensor assemblies

Monitor Specifications

- Supply Voltage: 12-35 Volts DC or 120/240 Volts AC
- Temperature: -30 to 70 C
- Channels: 4 channels with individually configurable set-points
- Relays: Three dry-contact (5 Amp) with 4 Amp fuses
- Radio Options: 2.4 GHz ISM, 100 mW, 3 miles Line-of-Site
900 MHz 200 mW
- Unit Address: 1-52 networks (1-78 for 2.4 GHz);
1-255 addresses per network
- Power Consumption: Nominal: 100mA @ 12 VDC in a static condition
- Radio Transmission: Every 1 minute with no change from sensor
Every 5 seconds with change from sensor
- Enclosure: 8 x 8 x 4 Integra
- Warranty: One year (limited)

OI-7543K Gen II WireFree Monitor/Sensor Assembly Kit

Monitor Dimensions

