

# TM-L90 Plus

## Liner-free Compatible Label Printer



# Cost-effective, liner-free label printing for QSRs and food service.

**Compatible** — uses NCR Sticky Media<sup>™</sup> liner-free adhesive labels

Efficient — improves order accuracy and customer satisfaction

**Convenient** — built-in USB for flexible connectivity

**Fast** — print speeds of up to 170 mm/sec

**Cost-effective** — enhanced print options reduce paper usage up to 30 percent

**Versatile** — 40, 58 and 80 mm print width support

**Smart** — automatically detects media type and paper width

**Energy-efficient** — reduced power consumption

C31C412A7971



### TM-L90 Plus Liner-free Compatible Label Printer

#### **Printer**

Print method Thermal line printing

Print speed 170 mm/sec (thermal receipt); 90 mm/sec (label

media)

Print resolution 203 x 203 dpi

Print font Font (A/B)

**40 mm:** 12 x 24, 7 x 17 / 9 x 17, 7 x 17 **58mm:** 13 x 24, 10 x 17 / 10 x 17, 7 x 17 **80mm:** TM-T88 compatible mode 13 x 24 / 10 x 17;

TM-L90 compatible mode 12 x 24 / 9 x 17 **Column capacity** 64/48 columns

Character size 1.13 x 2.13 / 1.5 x 3.0 / 1.0 x 2.0 mm (W x H)
Character set 95 Alphanumeric, 37 International, 128 x 11

Granhic

Barcode UPC-A, UPC-E, JAN8 (EAN), JAN13 (EAN), ITF, CODE39, CODE93, CODE128, CODABAR, PDF417,

MAXICODE, QR Code

Reliability MTBF 360,000 hours, MCBF 70 million lines (receipts),

35 million lines (labels)

Autocutter: 2 million cuts (receipts), 1 million cuts (labels)

#### Media

Paper width 40 mm, 80 mm, 58 mm Paper diameter 4" (102 mm)

Media thickness 2 mil to 8 mil, depending on media type

#### **General Information**

Interface Built-in USB interface + another selection; serial RS-232c, parallel IEEE-1284, Ethernet, Powered USB, Wireless

**Data buffer** 4K or 45 bytes

Power 24 VDC±7%

Power consumption Approx. 1.7A (mean)

D.K.D. function 2 drawers

Color Epson Dark Gray, Epson Cool White

Factory options PS-180 AC adapter, paper roll spacer,

wall-hanging bracket WH-10

Environmental standards WEEE, RoHS compliant

EMI standards VCCI class A, FCC/ICES-003 Class A, CE marking,

Canada EMI, AS/NZS CISPR22 Class A **Safety standards** UL, CSA, TÜV (EN60950) **Warranty** One-year limited warranty

**Overall dimensions (W x D x H)** 5.5" x 5.8" x 7.9" (140 mm x 148 mm x 203 mm)

Weight Approx. 4.19 lb (1.9 kg)

# 7.9"

#### What's in the Box

Ethernet, Built-in USB

TM-L90 Plus LFC Printer, Thermal roll paper (starter roll for operation check), User Guide, Power supply with AC cable

#### **Ordering Information\***

EDG (Epson Dark Gray)^^	
Serial, Built-in USB	C31C412A7991
EDG (Epson Dark Gray)**	
NCR Sticky Media, 40 mm	9023-1257
NCR Sticky Media, 58 mm	9023-1823
NCR Sticky Media, 80 mm	9023-1253

\*Contact your Epson representative for additional models.

\*\*Includes AC adapter (PS-180-343)

Better Products for a Better Future eco.epson.com



**Epson America, Inc.** 3840 Kilroy Airport Way, Long Beach, CA 90806 **Epson Canada Limited** 

185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. SmartWay is a service mark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/ or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2015 Epson America, Inc. Com-SS-Oct-13 CPD-50316 8/15