



SAFETY DATA SHEET

Issuing Date: no data available

Revision Date: 30-Dec-2017

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: PH-34

Product Name: POLYURETHANE CURING SOLUTION

Hentzen Coatings, Inc.
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200
Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use Industrial paint (Paint or Paint-Related), Restricted to professional users

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)


Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 2
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 2

Label Elements

Emergency Overview

DANGER

Hazard Statements
 Causes skin irritation
 Causes serious eye irritation
 May cause allergy or asthma symptoms or breathing difficulties if inhaled
 May cause an allergic skin reaction
 Suspected of causing cancer
 Suspected of damaging fertility or the unborn child
 May cause damage to organs through prolonged or repeated exposure
 Highly flammable liquid and vapor



Appearance Opaque **Physical state** Liquid **Odor** Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling
 In case of inadequate ventilation wear respiratory protection
 Contaminated work clothing should not be allowed out of the workplace
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/Bond container and receiving equipment
 Use explosion-proof electrical/ ventilating/ lighting/ equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool
 Store in accordance with local regulations

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

- May be harmful if swallowed
- May be harmful in contact with skin
- Harmful to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains a known or suspected carcinogen

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE	28182-81-2	50% - 60%	N/A	N/A
METHYL ETHYL KETONE	78-93-3	10% - 20%	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m ³
BUTYL ACETATE	123-86-4	5% - 10%	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m ³
METHYL AMYL KETONE	110-43-0	1% - 5%	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³
CYCLOHEXANONE	108-94-1	1% - 5%	STEL: 50 ppm TWA: 20 ppm S*	TWA: 50 ppm TWA: 200 mg/m ³
METHYL ISOBUTYL KETONE	108-10-1	1% - 5%	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³
ACETYLACETONE	123-54-6	1% - 5%	TWA: 25 ppm S*	N/A
TOLUENE	108-88-3	1% - 5%	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm

HEXAMETHYLENE DIISOCYANATE MONOMER	822-06-0	0% - 1%	TWA: 0.005 ppm	N/A
------------------------------------	----------	---------	----------------	-----

4. FIRST AID MEASURES

First Aid Measures

General advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water. Consult a physician if necessary. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
Inhalation	Asthma-like and/ or skin allergy-like symptoms.
Ingestion	Clean mouth with water and afterwards drink plenty of water.
Self-protection of the first aider	Remove all sources of ignition.
Most important symptoms and effects, both acute and delayed	
Most Important Symptoms and Effects	No information available.
Indication of any immediate medical attention and special treatment needed	
Notes to physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

Specific hazards arising from the chemical

Extremely flammable. Containers may explode when heated or if contaminated with water.

Explosion Data

Sensitivity to Mechanical Impact no data available.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment as required. Avoid breathing vapors or mists. Ventilate the area.
Other information	DECONTAMINATION SOLUTION: Concentrated ammonia (3 - 8%), detergent (2%) and water (90 - 95%), a solution of Union Carbide's Tergitol TMN-10 (20%) and water (80%) or a solution of 50% isopropanol, 45% water, and 5% concentrated ammonia solution(% by weight).

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Methods and materials for containment and cleaning up

Methods for Containment Decontaminate floor with decontamination solution letting stand for at least 15 minutes. Soak up with inert absorbent material.

Methods for Cleaning Up Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks and flame. Protect from moisture.

Incompatible Products Water. Glycol ethers. Alcohols. Epoxies. Bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH	OSHA	NIOSH IDLH
TERTIARY BUTYL ACETATE 540-88-5	STEL: 150 ppm TWA: 50 ppm	TWA: 200 ppm TWA: 950 mg/m ³	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m ³
METHYL ETHYL KETONE 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³
BUTYL ACETATE 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
METHYL AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m ³
CYCLOHEXANONE 108-94-1	STEL: 50 ppm TWA: 20 ppm S*	TWA: 50 ppm TWA: 200 mg/m ³	IDLH: 700 ppm TWA: 25 ppm TWA: 100 mg/m ³
ACETYLACETONE 123-54-6	TWA: 25 ppm S*	N/A	
METHYL ISOBUTYL KETONE 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm

			STEL: 300 mg/m ³
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
HEXAMETHYLENE DIISOCYANATE MONOMER 822-06-0	TWA: 0.005 ppm	N/A	Ceiling: 0.020 ppm 10 min Ceiling: 0.140 mg/m ³ 10 min TWA: 0.005 ppm TWA: 0.035 mg/m ³

NIOSH IDLH: Immediately Dangerous to Life or Health

Exposure controls

Engineering Measures

Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

If splashes are likely to occur, wear safety glasses with side-shields.

Skin and Body Protection

Chemical resistant apron.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Appearance	Opaque
Odor	Solvent.	Odor Threshold	No data available
pH	No data available	Flash Point	16 °F / -9 °C
Decomposition temperature	No data available	Boiling Point	175 °F / 79 °C
Melting Point / Melting Range	No data available	Freezing Point	No data available
Vapor Pressure @20°C (kPa)	No data available	Partition coefficient:	No data available
Vapor Density	No data available	Density	No data available
Bulk density	No data available	Specific Gravity	1.00
Evaporation Rate	No data available	Water solubility	No data available
Dynamic viscosity	No data available	Weight per Gallon (lbs/gal):	8.33
		Flammability Limits in Air	
		Upper	3.86 %
		Lower	0.61 %

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Water. Glycol ethers. Alcohols. Epoxies. Bases.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	The product has not been tested
Inhalation	There is no data for this product.
Eye Contact	There is no data for this product.
Skin Contact	There is no data for this product.
Ingestion	There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE 28182-81-2	N/A	N/A	= 18500 mg/m ³ (Rat) 1 h
TERTIARY BUTYL ACETATE 540-88-5	= 4100 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 9482 mg/m ³ (Rat) 4 h
METHYL ETHYL KETONE 78-93-3	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
BUTYL ACETATE 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
METHYL AMYL KETONE 110-43-0	= 1600 mg/kg (Rat)	= 12.6 mL/kg (Rabbit)	2000 - 4000 ppm (Rat) 6 h
CYCLOHEXANONE 108-94-1	= 1544 mg/kg (Rat)	= 947 mg/kg (Rabbit)	= 8000 ppm (Rat) 4 h
ACETYLACETONE 123-54-6	= 570 mg/kg (Rat) = 760 mg/kg (Rat)	= 1370 mg/kg (Rabbit) = 790 mg/kg (Rabbit)	= 1224 ppm (Rat) 4 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
HEXAMETHYLENE DIISOCYANATE MONOMER 822-06-0	= 710 µL/kg (Rat)	= 593 mg/kg (Rabbit)	= 0.06 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

MUTAGENIC EFFECTS No information available.

Carcinogenicity This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
CYCLOHEXANONE 108-94-1	A3	Group 3	N/A	N/A
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	N/A	X
TOLUENE 108-88-3	N/A	Group 3	N/A	N/A

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity	No information available.
Specific target organ systemic toxicity (single exposure)	No information available.
Specific target organ systemic toxicity (repeated exposure)	No information available.
Chronic Toxicity	May cause adverse liver effects.
Target Organ Effects	Central nervous system (CNS), Eyes, Kidney, Liver, Peripheral Nervous System (PNS), Respiratory system, Skin.
Aspiration hazard	No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	2302 mg/kg
ATEmix (dermal)	2742 mg/kg
ATEmix (inhalation-dust/mist)	7.2 mg/l
Oral LD50	5203 mg/kg (rat) Estimated
Dermal LD50	6173 mg/kg (rat) Estimated

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
TERTIARY BUTYL ACETATE 540-88-5	N/A	296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
METHYL ETHYL KETONE 78-93-3	N/A	3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through	4025 - 6440: 48 h Daphnia magna mg/L EC50 Static 5091: 48 h Daphnia magna mg/L EC50 520: 48 h Daphnia magna mg/L EC50
BUTYL ACETATE 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Lepomis macrochirus mg/L LC50 static	N/A
METHYL AMYL KETONE 110-43-0	N/A	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
CYCLOHEXANONE 108-94-1	N/A	481 - 578: 96 h Pimephales promelas mg/L LC50 flow-through 8.9: 96 h Pimephales promelas mg/L LC50	N/A
ACETYLACETONE 123-54-6	N/A	50.3 - 71.8: 96 h Lepomis macrochirus mg/L LC50 flow-through 64.1 - 80.1: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 98.3 - 110: 96 h Pimephales promelas mg/L LC50 flow-through	34.4: 48 h Daphnia magna mg/L EC50
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
TOLUENE 108-88-3	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 12.6: 96 h Pimephales promelas mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 54: 96 h Oryzias latipes mg/L LC50 static	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50

HEXAMETHYLENE DIISOCYANATE MONOMER 822-06-0	N/A	26.1: 96 h Brachydanio rerio mg/L LC50 static	N/A
---	-----	--	-----

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
METHYL ETHYL KETONE 78-93-3	0.3
BUTYL ACETATE 123-86-4	1.81
METHYL AMYL KETONE 110-43-0	1.98
CYCLOHEXANONE 108-94-1	0.86
METHYL ISOBUTYL KETONE 108-10-1	1.19
ACETYLACETONE 123-54-6	0.34
TOLUENE 108-88-3	2.7

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Waste treatment methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

US EPA Waste Number

D001

Chemical Name	RCRA - Basis for Listing	RCRA - D Series Wastes
METHYL ETHYL KETONE 78-93-3	Included in waste streams: F005, F039	200.0 mg/L regulatory level
CYCLOHEXANONE 108-94-1	Included in waste stream: F039	N/A
METHYL ISOBUTYL KETONE 108-10-1	Included in waste stream: F039	N/A
TOLUENE 108-88-3	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	N/A

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
TOLUENE 108-88-3	N/A	N/A	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	N/A

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
METHYL ETHYL KETONE 78-93-3	Toxic mixture of acetone, methyl acetate, and methyl alcohol Ignitable mixture of acetone, methyl acetate, and methyl alcohol
BUTYL ACETATE 123-86-4	Toxic
TOLUENE 108-88-3	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28
Description UN1263, Paint, 3, II, RQ
Emergency Response Guide Number 128

TDG

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Description UN1263, Paint, 3, II

MEX

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Description UN1263, Paint, 3, II

ICAO

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Special Provisions A3, A72
Description UN1263, Paint, 3, II

IATA

UN-No UN1263
Hazard class 3
Packing Group II
ERG Code 3L
Special Provisions A3, A72, A192

IMDG/IMO

UN-No UN1263
Hazard class 3
Packing Group II
EmS-No F-E, S-E
Special Provisions 163, 367

RID

UN-No UN1263
Proper shipping name Paint

Hazard class 3
Packing Group II
Classification Code F1
Description UN1263, Paint, 3, II

ADR/RID

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Classification Code F1
Tunnel restriction code (D/E)
Special Provisions 163, 640C, 650, 367
Description UN1263, Paint, 3, II, (D/E)
ADR/RID-Labels 3

ADN

Proper shipping name Paint
Hazard class 3
Packing Group II
Classification Code F1
Special Provisions 163, 640C, 650
Description UN1263, Paint, 3, II
Hazard Labels 3
Limited Quantity (LQ) 5 L
Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Complies
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
METHYL ISOBUTYL KETONE	108-10-1	1.0
TOLUENE	108-88-3	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard Yes
Sudden Release of Pressure Hazard No

Reactive Hazard

No

CAA (Clean Air Act)

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
METHYL ISOBUTYL KETONE	108-10-1	Present
TOLUENE	108-88-3	Present
HEXAMETHYLENE DIISOCYANATE MONOMER	822-06-0	Present

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TERTIARY BUTYL ACETATE	N/A	N/A	N/A	X
BUTYL ACETATE	5000 lb	N/A	N/A	X
TOLUENE	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
TERTIARY BUTYL ACETATE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ETHYL KETONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
BUTYL ACETATE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
CYCLOHEXANONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE	1000 lb 1 lb	N/A	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
HEXAMETHYLENE DIISOCYANATE MONOMER	100 lb	N/A	RQ 100 lb final RQ RQ 45.4 kg final RQ

State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
METHYL ISOBUTYL KETONE	108-10-1	Carcinogen Developmental
TOLUENE	108-88-3	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
TERTIARY BUTYL ACETATE	X	X	X	N/A	N/A
METHYL ETHYL KETONE	X	X	X	X	N/A
BUTYL ACETATE	X	X	X	N/A	N/A
METHYL AMYL KETONE	X	X	X	N/A	N/A
CYCLOHEXANONE	X	X	X	X	N/A
ACETYLACETONE	X	X	X	N/A	N/A

METHYL ISOBUTYL KETONE	X	X	X	X	N/A
TOLUENE	X	X	X	X	X

International Regulations


Mexico - Grade Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
TERTIARY BUTYL ACETATE	N/A	Mexico: TWA 200 ppm Mexico: TWA 950 mg/m ³ Mexico: STEL 250 ppm Mexico: STEL 1190 mg/m ³
METHYL ETHYL KETONE	N/A	Mexico: TWA 200 ppm Mexico: TWA 590 mg/m ³ Mexico: STEL 300 ppm Mexico: STEL 885 mg/m ³
BUTYL ACETATE	N/A	Mexico: TWA 150 ppm Mexico: TWA 710 mg/m ³ Mexico: STEL 200 ppm Mexico: STEL 950 mg/m ³
METHYL AMYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 235 mg/m ³ Mexico: STEL 100 ppm Mexico: STEL 465 mg/m ³
CYCLOHEXANONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 200 mg/m ³ Mexico: STEL 100 ppm Mexico: STEL 400 mg/m ³
METHYL ISOBUTYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 205 mg/m ³ Mexico: STEL 75 ppm Mexico: STEL 307 mg/m ³
TOLUENE	N/A	Mexico: TWA 50 ppm Mexico: TWA 188 mg/m ³

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 3 Instability 0 Physical and Chemical Hazards -

NFPA Rating



HMIS Health Hazard 2 * Flammability 3 Physical Hazard 1 Personal protection X

Chronic Hazard Star Legend

* Chronic Health Hazard

Revision Date: 30-Dec-2017

Revision Note
No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the

date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. PH-34GV

end