



SAFETY DATA SHEET

Issuing Date: 15-Apr-2016

Revision Date: 30-Dec-2017

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: PS-6-G50

Product Name: HIGH SOLIDS POLYURETHANE TOPCOAT SEMIGLO PEARL GRAY

Hentzen Coatings, Inc.
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200

Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use

Industrial paint (Paint or Paint-Related), Restricted to professional users

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 1B
Flammable Liquids	Category 2

Label Elements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation
Causes serious eye irritation
May cause genetic defects
May cause cancer
May damage fertility or the unborn child
Highly flammable liquid and vapor



Appearance Opaque

Physical state Liquid

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection
Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed
 Ground/Bond container and receiving equipment
 Use explosion-proof electrical/ ventilating/ lighting/ equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool
 Store in accordance with local regulations

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

- May be harmful if swallowed
- May be harmful in contact with skin
- Harmful to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains a known or suspected carcinogen

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
TITANIUM DIOXIDE	13463-67-7	30% - 40%	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust
METHYL AMYL KETONE	110-43-0	10% - 20%	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³
XYLENE(PURE)	1330-20-7	1% - 5%	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³
ACETYLACETONE	123-54-6	1% - 5%	TWA: 25 ppm S*	N/A
CYCLOHEXANONE	108-94-1	1% - 5%	STEL: 50 ppm TWA: 20 ppm S*	TWA: 50 ppm TWA: 200 mg/m ³
ETHYL ACETATE	141-78-6	1% - 5%	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³
ETHYLBENZENE	100-41-4	0% - 1%	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³
METHYL ISOBUTYL KETONE	108-10-1	0% - 1%	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³
ALIPHATIC PETROLEUM DISTILLATES	64742-89-8	0% - 1%	N/A	N/A
CARBON BLACK	1333-86-4	0% - 1%	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³
DIBUTYLTIN DILAURATE	77-58-7	0% - 1%	STEL: 0.2 mg/m ³ Sn TWA: 0.1 mg/m ³ Sn S*	TWA: 0.1 mg/m ³ Sn

4. FIRST AID MEASURES

First Aid Measures

General advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Eye Contact	Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with plenty of water.
Inhalation	Consult a physician if necessary. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.
Ingestion	Do NOT induce vomiting.
Self-protection of the first aider	Remove all sources of ignition.
Most important symptoms and effects, both acute and delayed	
Most Important Symptoms and Effects	No information available.
Indication of any immediate medical attention and special treatment needed	
Notes to physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

Specific hazards arising from the chemical

Extremely flammable.

Explosion Data

Sensitivity to Mechanical Impact no data available.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment as required. Avoid breathing vapors or mists. Ventilate the area.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Methods and materials for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks and flame.

Incompatible Products

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH IDLH
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
METHYL AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m ³
AMORPHOUS SILICA 7631-86-9	N/A	TWA: 20 mppcf : (80)/(% SiO ₂) mg/m ³ TWA	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
TERTIARY BUTYL ACETATE 540-88-5	STEL: 150 ppm TWA: 50 ppm	TWA: 200 ppm TWA: 950 mg/m ³	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m ³
XYLENE(PURE) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³	
ACETYLACETONE 123-54-6	TWA: 25 ppm S*	N/A	
CYCLOHEXANONE 108-94-1	STEL: 50 ppm TWA: 20 ppm S*	TWA: 50 ppm TWA: 200 mg/m ³	IDLH: 700 ppm TWA: 25 ppm TWA: 100 mg/m ³
ETHYL ACETATE 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³
ETHYLBENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³

			TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
DIBUTYL TIN DILAURATE 77-58-7	STEL: 0.2 mg/m ³ Sn TWA: 0.1 mg/m ³ Sn S*	TWA: 0.1 mg/m ³ Sn	IDLH: 25 mg/m ³ Sn TWA: 0.1 mg/m ³ except Cyhexatin Sn

NIOSH IDLH: Immediately Dangerous to Life or Health

Exposure controls

Engineering Measures Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Use personal protective equipment as required.

Skin and Body Protection Chemical resistant apron.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Appearance	Opaque
Odor	Solvent.	Odor Threshold	No data available
pH	No data available	Flash Point	12 °F / -11 °C
Decomposition temperature	No data available	Boiling Point	170 °F / 77 °C
Melting Point / Melting Range	No data available	Freezing Point	No data available
Vapor Pressure @20°C (kPa)	No data available	Partition coefficient:	No data available
Vapor Density	No data available	Density	No data available
Bulk density	No data available	Specific Gravity	1.33
Evaporation Rate	No data available	Water solubility	No data available
Dynamic viscosity	No data available	Weight per Gallon (lbs/gal):	11.05
		Flammability Limits in Air	
		Upper	2.94 %
		Lower	0.48 %

10. STABILITY AND REACTIVITY

Reactivity
No data available

Chemical stability
Stable under recommended storage conditions.

Conditions to Avoid
Extremes of temperature and direct sunlight.

Incompatible Materials
None known based on information supplied.

Hazardous Decomposition Products
None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	The product has not been tested
Inhalation	There is no data for this product.
Eye Contact	There is no data for this product.
Skin Contact	There is no data for this product.
Ingestion	There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg (Rat)	N/A	N/A
METHYL AMYL KETONE 110-43-0	= 1600 mg/kg (Rat)	= 12.6 mL/kg (Rabbit)	2000 - 4000 ppm (Rat) 6 h
AMORPHOUS SILICA 7631-86-9	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h
TERTIARY BUTYL ACETATE 540-88-5	= 4100 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 9482 mg/m ³ (Rat) 4 h
XYLENE(PURE) 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
ACETYLACETONE 123-54-6	= 570 mg/kg (Rat) = 760 mg/kg (Rat)	= 1370 mg/kg (Rabbit) = 790 mg/kg (Rabbit)	= 1224 ppm (Rat) 4 h
CYCLOHEXANONE 108-94-1	= 1544 mg/kg (Rat)	= 947 mg/kg (Rabbit)	= 8000 ppm (Rat) 4 h
ETHYL ACETATE 141-78-6	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit)	N/A
ETHYLBENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h
CARBON BLACK 1333-86-4	> 15400 mg/kg (Rat)	N/A	N/A
DIBUTYLTIN DILAURATE 77-58-7	= 45 mg/kg (Rat)	= 630 mg/kg (Rabbit)	N/A

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

MUTAGENIC EFFECTS No information available.

Carcinogenicity This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE 13463-67-7	N/A	Group 2B	N/A	X
AMORPHOUS SILICA 7631-86-9	N/A	Group 3	N/A	N/A
XYLENE(PURE) 1330-20-7	N/A	Group 3	N/A	N/A
CYCLOHEXANONE 108-94-1	A3	Group 3	N/A	N/A
ETHYLBENZENE 100-41-4	A3	Group 2B	N/A	X
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	N/A	X
CARBON BLACK	A3	Group 2B	N/A	X

1333-86-4			
-----------	--	--	--

Legend:

- ACGIH (American Conference of Governmental Industrial Hygienists)
- A3 - Animal Carcinogen
- IARC (International Agency for Research on Cancer)
- Group 2B - Possibly Carcinogenic to Humans
- Group 3 - Not Classifiable as to Carcinogenicity in Humans
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)
- X - Present

Reproductive Toxicity	No information available.
Specific target organ systemic toxicity (single exposure)	No information available.
Specific target organ systemic toxicity (repeated exposure)	No information available.
Chronic Toxicity	May cause adverse liver effects.
Target Organ Effects	Central nervous system (CNS), Eyes, Kidney, Liver, Lungs, Peripheral Nervous System (PNS), Respiratory system, Skin.
Aspiration hazard	No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	3191 mg/kg
ATEmix (dermal)	4216 mg/kg
ATEmix (inhalation-dust/mist)	5.8 mg/l
Oral LD50	3500 mg/kg (rat) Estimated
Dermal LD50	6094 mg/kg (rat) Estimated

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
METHYL AMYL KETONE 110-43-0	N/A	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
TERTIARY BUTYL ACETATE 540-88-5	N/A	296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
XYLENE(PURE) 1330-20-7	N/A	13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50	0.6: 48 h Gammarus lacustris mg/L LC50 3.82: 48 h water flea mg/L EC50
ACETYLACETONE 123-54-6	N/A	50.3 - 71.8: 96 h Lepomis macrochirus mg/L LC50 flow-through 64.1 - 80.1: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 98.3 - 110: 96 h Pimephales promelas mg/L LC50 flow-through	34.4: 48 h Daphnia magna mg/L EC50

CYCLOHEXANONE 108-94-1	N/A	481 - 578: 96 h Pimephales promelas mg/L LC50 flow-through 8.9: 96 h Pimephales promelas mg/L LC50	N/A
ETHYL ACETATE 141-78-6	N/A	220 - 250: 96 h Pimephales promelas mg/L LC50 flow-through 352 - 500: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 484: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	560: 48 h Daphnia magna mg/L EC50 Static
ETHYLBENZENE 100-41-4	1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
METHYL AMYL KETONE 110-43-0	1.98
XYLENE(PURE) 1330-20-7	3.15
ACETYLACETONE 123-54-6	0.34
CYCLOHEXANONE 108-94-1	0.86
ETHYL ACETATE 141-78-6	0.6
ETHYLBENZENE 100-41-4	3.2
METHYL ISOBUTYL KETONE 108-10-1	1.19

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste treatment methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

US EPA Waste Number

D001

Chemical Name	RCRA - Basis for Listing	RCRA - D Series Wastes
XYLENE(PURE) 1330-20-7	Included in waste stream: F039	N/A
CYCLOHEXANONE 108-94-1	Included in waste stream: F039	N/A
ETHYL ACETATE 141-78-6	Included in waste stream: F039	N/A
ETHYLBENZENE 100-41-4	Included in waste stream: F039	N/A

METHYL ISOBUTYL KETONE 108-10-1	Included in waste stream: F039	N/A
------------------------------------	--------------------------------	-----

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
XYLENE(PURE) 1330-20-7	Toxic Ignitable
ETHYL ACETATE 141-78-6	Toxic Ignitable
ETHYLBENZENE 100-41-4	Toxic Ignitable
DIBUTYLTIN DILAURATE 77-58-7	Toxic

14. TRANSPORT INFORMATION

DOT

UN-No UN1263
 Proper shipping name Paint
 Hazard class 3
 Packing Group II
 Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28
 Description UN1263, Paint, 3, II, RQ
 Emergency Response Guide Number 128

TDG

UN-No UN1263
 Proper shipping name Paint
 Hazard class 3
 Packing Group II
 Description UN1263, Paint, 3, II

MEX

UN-No UN1263
 Proper shipping name Paint
 Hazard class 3
 Packing Group II
 Description UN1263, Paint, 3, II

ICAO

UN-No UN1263
 Proper shipping name Paint
 Hazard class 3
 Packing Group II
 Special Provisions A3, A72
 Description UN1263, Paint, 3, II

IATA

UN-No UN1263
 Hazard class 3
 Packing Group II
 ERG Code 3L
 Special Provisions A3, A72, A192

IMDG/IMO

UN-No UN1263
 Hazard class 3
 Packing Group II

EmS-No F-E, S-E
Special Provisions 163, 367

RID

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Classification Code F1
Description UN1263, Paint, 3, II

ADR/RID

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Classification Code F1
Tunnel restriction code (D/E)
Special Provisions 163, 640C, 650, 367
Description UN1263, Paint, 3, II, (D/E)
ADR/RID-Labels 3

ADN

Proper shipping name Paint
Hazard class 3
Packing Group II
Classification Code F1
Special Provisions 163, 640C, 650
Description UN1263, Paint, 3, II
Hazard Labels 3
Limited Quantity (LQ) 5 L
Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Complies
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
XYLENE(PURE)	1330-20-7	1.0

ETHYLBENZENE	100-41-4	0.1
--------------	----------	-----

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CAA (Clean Air Act)

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
XYLENE(PURE)	1330-20-7	Present
ETHYLBENZENE	100-41-4	Present
METHYL ISOBUTYL KETONE	108-10-1	Present

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TERTIARY BUTYL ACETATE	N/A	N/A	N/A	X
XYLENE(PURE)	100 lb	N/A	N/A	X
ETHYLBENZENE	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
TERTIARY BUTYL ACETATE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE(PURE)	100 lb	N/A	RQ 100 lb final RQ RQ 45.4 kg final RQ
CYCLOHEXANONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL ACETATE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYLBENZENE	1000 lb	N/A	RQ 1000 lb final RQ RQ 454 kg final RQ
METHYL ISOBUTYL KETONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ

State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
TITANIUM DIOXIDE	13463-67-7	Carcinogen
ETHYLBENZENE	100-41-4	Carcinogen
METHYL ISOBUTYL KETONE	108-10-1	Carcinogen Developmental
CARBON BLACK	1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
---------------	---------------	------------	--------------	----------	--------------

TITANIUM DIOXIDE	X	X	X	N/A	X
METHYL AMYL KETONE	X	X	X	N/A	N/A
TERTIARY BUTYL ACETATE	X	X	X	N/A	N/A
XYLENE(PURE)	X	X	X	X	X
ACETYLACETONE	X	X	X	N/A	N/A
CYCLOHEXANONE	X	X	X	X	N/A
ETHYL ACETATE	X	X	X	N/A	N/A
ETHYLBENZENE	X	X	X	X	X
METHYL ISOBUTYL KETONE	X	X	X	X	N/A
CARBON BLACK	X	X	X	X	N/A
BUTYL ACETATE	X	X	X	N/A	X

International Regulations

Mexico - Grade

Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
TITANIUM DIOXIDE	N/A	Mexico: TWA 10 mg/m ³ Mexico: STEL 20 mg/m ³
METHYL AMYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 235 mg/m ³ Mexico: STEL 100 ppm Mexico: STEL 465 mg/m ³
TERTIARY BUTYL ACETATE	N/A	Mexico: TWA 200 ppm Mexico: TWA 950 mg/m ³ Mexico: STEL 250 ppm Mexico: STEL 1190 mg/m ³
XYLENE(PURE)	N/A	Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 150 ppm Mexico: STEL 655 mg/m ³
CYCLOHEXANONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 200 mg/m ³ Mexico: STEL 100 ppm Mexico: STEL 400 mg/m ³
ETHYL ACETATE	N/A	Mexico: TWA 400 ppm Mexico: TWA 1400 mg/m ³
ETHYLBENZENE	N/A	Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 125 ppm Mexico: STEL 545 mg/m ³
METHYL ISOBUTYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 205 mg/m ³ Mexico: STEL 75 ppm Mexico: STEL 307 mg/m ³
CARBON BLACK	N/A	Mexico: TWA 3.5 mg/m ³ Mexico: STEL 7 mg/m ³
DIBUTYLTIN DILAURATE	N/A	Mexico: TWA 0.1 mg/m ³ Mexico: STEL 0.2 mg/m ³

16. OTHER INFORMATION

NFPA

Health Hazard 2

Flammability 3

Instability 0

Physical and Chemical Hazards -

NFPA Rating



HMIS **Health Hazard 1 * Flammability 3 Physical Hazard 0 Personal protection X**

Chronic Hazard Star Legend

** Chronic Health Hazard*

Issuing Date: 15-Apr-2016

Revision Date: 30-Dec-2017

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. PS-6-G50GV

end



SAFETY DATA SHEET

Issuing Date: 23-Apr-2015

Revision Date: 30-Dec-2017

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: PH-37

Product Name: POLYURETHANE HARDENER

Hentzen Coatings, Inc.
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200
Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use Industrial paint (Paint or Paint-Related), Restricted to professional users

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)


Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 2
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Reproductive Toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

Label Elements

Emergency Overview

DANGER

Hazard Statements
 Causes skin irritation
 Causes serious eye irritation
 May cause allergy or asthma symptoms or breathing difficulties if inhaled
 May cause an allergic skin reaction
 Suspected of damaging fertility or the unborn child
 May cause damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Highly flammable liquid and vapor



Appearance Opaque **Physical state** Liquid **Odor** Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling
 In case of inadequate ventilation wear respiratory protection
 Contaminated work clothing should not be allowed out of the workplace
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/Bond container and receiving equipment
 Use explosion-proof electrical/ ventilating/ lighting/ equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool
 Store in accordance with local regulations

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

- May be harmful if swallowed
- Harmful to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains a known or suspected carcinogen

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE	28182-81-2	80% - 90%	N/A	N/A
TOLUENE	108-88-3	10% - 20%	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm
HEXAMETHYLENE DIISOCYANATE MONOMER	822-06-0	0% - 1%	TWA: 0.005 ppm	N/A

4. FIRST AID MEASURES

First Aid Measures**General advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing. If symptoms persist, call a

	physician.
Skin Contact	Wash off immediately with soap and plenty of water. Consult a physician if necessary. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
Inhalation	Consult a physician if necessary. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Asthma-like and/ or skin allergy-like symptoms.
Ingestion	Do NOT induce vomiting.
Self-protection of the first aider	Remove all sources of ignition.
Most important symptoms and effects, both acute and delayed	
Most Important Symptoms and Effects	No information available.
Indication of any immediate medical attention and special treatment needed	
Notes to physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

Specific hazards arising from the chemical

Containers may explode when heated or if contaminated with water. Flammable.

Explosion Data

Sensitivity to Mechanical Impact no data available.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Use personal protective equipment as required. Avoid breathing vapors or mists. Ventilate the area.

Other information DECONTAMINATION SOLUTION: Concentrated ammonia (3 - 8%), detergent (2%) and water (90 - 95%), a solution of Union Carbide's Tergitol TMN-10 (20%) and water (80%) or a solution of 50% isopropanol, 45% water, and 5% concentrated ammonia solution(% by weight).

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Methods and materials for containment and cleaning up

Methods for Containment Decontaminate floor with decontamination solution letting stand for at least 15 minutes. Soak up with inert absorbent material.

Methods for Cleaning Up Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks and flame. Protect from moisture.

Incompatible Products Water. Glycol ethers. Alcohols. Epoxies. Bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH IDLH
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
HEXAMETHYLENE DIISOCYANATE MONOMER 822-06-0	TWA: 0.005 ppm	N/A	Ceiling: 0.020 ppm 10 min Ceiling: 0.140 mg/m ³ 10 min TWA: 0.005 ppm TWA: 0.035 mg/m ³

NIOSH IDLH: Immediately Dangerous to Life or Health

Exposure controls

Engineering Measures Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Use personal protective equipment as required.

Skin and Body Protection Chemical resistant apron.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Appearance	Opaque
Odor	Solvent.	Odor Threshold	No data available
pH	No data available	Flash Point	45 °F / 7 °C
Decomposition temperature	No data available	Boiling Point	183 °F / 84 °C
Melting Point / Melting Range	No data available	Freezing Point	No data available
Vapor Pressure @20°C (kPa)	No data available	Partition coefficient:	No data available
Vapor Density	No data available	Density	No data available
Bulk density	No data available	Specific Gravity	1.12
Evaporation Rate	No data available	Water solubility	No data available
Dynamic viscosity	No data available	Weight per Gallon (lbs/gal):	9.35
		Flammability Limits in Air	
		Upper	0.71 %
		Lower	0.12 %

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Water. Glycol ethers. Alcohols. Epoxies. Bases.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	The product has not been tested
Inhalation	There is no data for this product.
Eye Contact	There is no data for this product.
Skin Contact	There is no data for this product.
Ingestion	There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE 28182-81-2	N/A	N/A	= 18500 mg/m ³ (Rat) 1 h
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
HEXAMETHYLENE DIISOCYANATE MONOMER 822-06-0	= 710 µL/kg (Rat)	= 593 mg/kg (Rabbit)	= 0.06 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

MUTAGENIC EFFECTS

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	N/A	Group 3	N/A	N/A

Legend:*IARC (International Agency for Research on Cancer)**Group 3 - Not Classifiable as to Carcinogenicity in Humans***Reproductive Toxicity**

No information available.

Specific target organ systemic toxicity (single exposure)

No information available.

Specific target organ systemic toxicity (repeated exposure)

No information available.

Chronic Toxicity

May cause adverse liver effects.

Target Organ Effects

Central nervous system (CNS), Eyes, Kidney, Liver, Respiratory system, Skin.

Aspiration hazard

No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2647 mg/kg

ATEmix (dermal) 12216 mg/kg

ATEmix (inhalation-dust/mist) 28.3 mg/l

Oral LD50 24450 mg/kg (rat) Estimated

Dermal LD50 88496 mg/kg (rat) Estimated

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
TOLUENE 108-88-3	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 12.6: 96 h Pimephales promelas mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 54: 96 h Oryzias latipes mg/L LC50 static	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
HEXAMETHYLENE DIISOCYANATE MONOMER 822-06-0	N/A	26.1: 96 h Brachydanio rerio mg/L LC50 static	N/A

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
TOLUENE 108-88-3	2.7

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste treatment methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

US EPA Waste Number D001

Chemical Name	RCRA - Basis for Listing	RCRA - D Series Wastes
TOLUENE 108-88-3	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	N/A

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
TOLUENE 108-88-3	N/A	N/A	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	N/A

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
TOLUENE 108-88-3	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28
Description UN1263, Paint, 3, II, RQ
Emergency Response Guide Number 128

TDG

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Description UN1263, Paint, 3, II

MEX

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Description UN1263, Paint, 3, II

ICAO

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Special Provisions	A3, A72
Description	UN1263, Paint, 3, II

IATA

UN-No	UN1263
Hazard class	3
Packing Group	II
ERG Code	3L
Special Provisions	A3, A72, A192

IMDG/IMO

UN-No	UN1263
Hazard class	3
Packing Group	II
EmS-No	F-E, S-E
Special Provisions	163, 367

RID

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Description	UN1263, Paint, 3, II

ADR/RID

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Tunnel restriction code	(D/E)
Special Provisions	163, 640C, 650, 367
Description	UN1263, Paint, 3, II, (D/E)
ADR/RID-Labels	3

ADN

Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II
Hazard Labels	3
Limited Quantity (LQ)	5 L
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
TOLUENE	108-88-3	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CAA (Clean Air Act)

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
TOLUENE	108-88-3	Present
HEXAMETHYLENE DIISOCYANATE MONOMER	822-06-0	Present

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
TOLUENE	1000 lb 1 lb	N/A	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
HEXAMETHYLENE DIISOCYANATE MONOMER	100 lb	N/A	RQ 100 lb final RQ RQ 45.4 kg final RQ

State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
TOLUENE	108-88-3	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
TOLUENE	X	X	X	X	X

International Regulations


Mexico - Grade Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
TOLUENE	N/A	Mexico: TWA 50 ppm Mexico: TWA 188 mg/m ³

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 3 Instability 0 Physical and Chemical Hazards -

NFPA Rating



HMIS Health Hazard 2 * Flammability 3 Physical Hazard 1 Personal protection X

Chronic Hazard Star Legend * *Chronic Health Hazard*

Issuing Date: 23-Apr-2015
Revision Date: 30-Dec-2017
Revision Note
 No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. PH-37GV

end