



Product: 36 Inch Wall Mount Range Hood

Model Number: HRH3607

BLOWER RATING

| BLOWER RATINGS | CFM | SONES (DB) |
|----------------|---------|------------|
| Low | 300 CFM | 56 |
| Medium | 420 CFM | 63 |
| High | 600 CFM | 64 |

PRODUCT DIMENSIONS

| | |
|---------------------|--|
| Range Hood Size | 36 |
| Product Width (in) | 36 |
| Product Depth (in) | 19 |
| Product Height (in) | 11 7/8" (w/out duct covers) 45.5" (including duct covers) |
| Duct Length (in) | 34 |
| Duct Size (in) | Diameter:6 |
| Duct Shape | Round |
| Gross Weight (lb.) | 41.8 |
| Net Weight (lb.) | 30.2 |



FEATURES & BENEFITS

- + **Multiple Fan Speeds** - 3 fan speeds allow for easy adjustment between high, medium and low suction
- + **LED Lighting** - Two 3.5-watt LED lights to illuminate your cooking area and save energy
- + **Quiet 60dB Operation** - Quiet operation keeps noise level at a maximum 60 decibels
- + **Convertible** - Vent out or recirculating (ductless) option with carbon filters (not included)
- + **Commercial-style Baffle Filter** - Large, commercial-style 430 grade stainless steel baffle filter maximizes air flow and grease filtering while the hood is in operation
- + **Touch Control with Digital Display** - Features touch control with integrated backlit digital display that shows clock and a reminder to clean filters
- + **600 CFM of Suction** - 600 CFM of suction effectively removes odors, smoke, grease and moisture from your cooking area
- + **Stainless Steel Finish** - Stainless steel finish offers modern design aesthetic and is built to withstand high heat, grease, oil and steam
- + **Remote Control** - Remote control allows for adjusting fan speed and lighting from anywhere in the kitchen
- + **Duct Cover Included:** The stainless steel duct cover matches the linear styling of the THOR kitchen professional 36 Inch vent hood and extends the height of the hood for 9 foot ceilings

TECHNICAL DETAILS

| | |
|--------------------|--------------------------|
| Lighting | Dual 3.5W GU10 LED light |
| Noise level (Max.) | 60 dB |
| Filter type | 430SS Baffle filter |
| Control type | Remote control |
| Fan Speeds | 3 speed |
| Frequency | 60HZ |
| CFM | 600 |
| Voltage | 120V |
| Wattage | 337W |

WARRANTY: ONE YEAR LIMITED WARRANTY





INSTALLATION & SPEC

INSTALLTION DRILLING AND LINING

1. Draw a vertical line on the supporting wall up to the ceiling, or as high as practical, at the centre of the area in which the hood will be installed.
2. Draw a horizontal line 28-30 inches above an electric top or 30-32 inches above a gas top.
3. Place chimney mounting brackets on the wall as shown about 1" (27mm) from the ceiling or upper limit aligning the centre (notch) with the vertical reference line.

