

FULGOR

MILANO

600 Series Fully Intergrated Hidden Control

F6DW24FI1



Series	600
Type	FULLY INTEGRATED
Size	24" Tall Tube
Colour	N/A
PERFORMANCES	
PLACE SETTINGS	13
ENERGY CONSUMPTION (kWh / year)	265
WATER CONSUMPTION l	12
WATER CONSUMPTION (l / year)	3360
NOISE	50dB
CONTROLS	
FRONTAL PANEL COLOR	Black
PUSH BUTTON COLOR	Black
PROGRAM SELECTOR	Push buttons
PROGRAM GAUGE	RED
TEMPERATURE	38°-45°-55°-65°-70°
No OF BUTTONS	5
DELAY TIMER	Yes Display 1 digit 9h
GAUGES	
ON / OFF gauge	yes
RINSE AID LEVEL GAUGE	Light
ACOUSTIC SIGNAL AT THE END	Yes
PROGRAMMES	
No OF WASH CYCLES	9
PROGRAMME 1	Soak
PROGRAMME 2	Light
PROGRAMME 3	Normative_USA
PROGRAMME 4	Auto 40 50
PROGRAMME 5	Super
PROGRAMME 6	FAST CYCLES
PROGRAMME 7	FAST CYCLES
PROGRAMME 8	FAST CYCLES
PROGRAMME 9	FAST CYCLES
HALF LOAD	DISTRIBUTED AS PROGRAM
SANITIZATION	Yes program
FEATURES	
TUB MATERIAL	stainless steel
INTERNAL DOOR	stainless steel
LOWER SPRAY ARM	Normal
TOP SPRAY ARM	Yes
ACQUASTOP	Full
HEATING ELEMENT	Concealed heating element
TURBIDINESS SENSOR	Yes

FULGOR

MILANO

HYDRAULIC CONNECTION	Hot/cold
HINGES	FIXED FULCRUM NOT ADJUSTABLE
REAR FOOT ADJUSTEMENT	Yes
SINGLE LOAD	4.0 - Pressure switch
LENGHT OF INLET HOSE	172
LENGHT OF DRAIN HOSE	170
WATER HARDNESS MAX	100°FH;58°dH
T MAX WATER INLET	60

BASKETS

BASKETS COLOR	Grey
LOWER BASKET	13 Place settings double holde
UPPER BASKET	MIDDLE
UPPER BASKET ADJUSTEMENT	Automatic 3 levels
CUTLERY BASKET	13 SETTINGS

DOCUMENTATION

APPROVAL	UL trhough ETL
----------	----------------

Dimensions/Weight

Overall dim - width	23 9/16" (598 mm)
Overall dim - height	23 3/16" (589 mm)
Overall dim - depth	33 13/16" - 35 3/4" (860 - 910)
Cutout - width	23 5/8" (600 mm)
Cutout - height (min)	33 7/8" (860 mm)
Cutout - depth (min)	22 5/8" (575 mm)
Gross (Net) weight	46 (44) kg

Power / Ratings (115 V, 60 Hz)

KW/Amps rating	1400W - 13 A
Power cord + Plug	yes

INSTRUCTIONS FOR USE

Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR